


Pas klinowy Z/10

Hi-Power® - profil klasyczny, spłaszczony



Materiał

Polichloropren



	Szer. b	Wys. h
Z	10	6

Z/10

Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość
T09527	Z 17,5	450	F06367	Z 31,5	800	F06381	Z 46	1180
T09528	Z 18,5	475	F06368	Z 32,5	825	F06382	Z 47	1200
T37035	Z 19	485	F06369	Z 33,5	850	F06383	Z 48	1225
T09529	Z 19,5	500	F06370	Z 34,5	875	F06384	Z 48,5	1230
F05589	Z 20,5	530	F06371	Z 35,5	900	F05327	Z 49	1250
F06357	Z 22	560	F06372	Z 36	910	F06385	Z 50	1275
F06358	Z 22,5	575	F06373	Z 37	935	F06386	Z 51	1300
F06359	Z 23,5	600	F06374	Z 37,5	950	T53970	Z 52	1320
F06360	Z 24	610	F06375	Z 38,5	975	T53989	Z 55	1400
F06361	Z 25	630	F06376	Z 39	980	T53993	Z 57	1450
F06362	Z 26,5	670	F05762	Z 39,5	1000	T53995	Z 59	1500
F05761	Z 28	710	F06377	Z 41,5	1050	F06387	Z 63,5	1600
F06363	Z 29	730	F06378	Z 42	1060	T54007	Z 67	1700
F06364	Z 29,5	750	T09222	Z 44	1120	T54010	Z 71	1800
F06365	Z 30,5	775	F06379	Z 45	1150	T54012	Z 75	1900
F06366	Z 31	785	F06380	Z 45,5	1160			

Rozmiary w mm.

UWAGA:

Koła pasowe patrz strona J5 - J7.


Pas klinowy A/13

Hi-Power® - profil klasyczny, spłaszczony



Materiał

Polichloropren



	Szer. b	Wys. h
A	13	8

A/13-MN

Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość
F06163	A 21	535	F05542	A 63	1600	T37071	A 130	3310
F06164	A 22	560	F06198	A 64	1625	T37072	A 134	3410
F06165	A 23	590	F05406	A 65	1655	T37074	A 136	3455
F06166	A 23,5	600	F06199	A 66	1680	T18241	A 140	3550
F06167	A 24	615	F06200	A 67	1700	T37073	A 144	3660
F06168	A 24,5	630	F05725	A 68	1730	T18244	A 147	3750
F06169	A 25	650	T37053	A 69	1760	T18245	A 158	4000
F05758	A 26	670	F06201	A 70	1780	T37075	A 173	4400
F06170	A 27	690	F06202	A 71	1800	T37076	A 180	4575
F06171	A 27,5	700	F06203	A 72	1830			
F06172	A 28	710	F06204	A 73	1860			
F06173	A 28,5	725	F06205	A 74	1880			
F06174	A 29,5	750	F06206	A 75	1900			
F06175	A 30	775	F06207	A 76	1930			
F06176	A 31	800	F06208	A 77	1960			
F05094	A 32	825	F06209	A 78	1980			
F06177	A 33	850	F02831	A 79	2000			
F06178	A 34	875	F06210	A 80	2040			
F05096	A 35	900	F06211	A 81	2060			
F05185	A 36	925	F06212	A 82	2090			
F06179	A 37	950	F06213	A 83	2120			
F05383	A 38	975	F06214	A 84	2140			
F06180	A 39	1000	F06215	A 85	2160			
F06181	A 40	1030	F06216	A 86	2200			
F05264	A 41	1050	F06217	A 87	2215			
F06182	A 41,5	1060	F06218	A 88	2240			
F06183	A 42	1075	F06219	A 89	2265			
F06184	A 43	1100	F06220	A 90	2300			
F06185	A 44	1125	F06221	A 91	2320			
F06186	A 45	1150	F06222	A 92	2345			
F06187	A 46	1180	F06223	A 93	2360			
F06188	A 47	1200	F06224	A 94	2400			
F05263	A 48	1225	F06225	A 95	2420			
F06189	A 49	1250	F06226	A 96	2440			
F06190	A 50	1275	F06227	A 97	2475			
F06191	A 51	1300	F06228	A 98	2500			
F06192	A 52	1320	F06229	A 100	2540			
F05407	A 53	1350	F06230	A 102	2590			
F05100	A 54	1375	F06231	A 104	2650			
F05280	A 55	1400	F06232	A 105	2670			
F05153	A 56	1430	F06233	A 108	2750			
F06193	A 57	1450	F06234	A 110	2800			
F06194	A 58	1475	F06235	A 112	2850			
F04261	A 59	1500	T18233	A 118	3000			
F06195	A 60	1525	T18234	A 120	3050			
F06196	A 61	1550	T18235	A 124	3150			
F06197	A 62	1575	T16361	A 128	3250			

Rozmiary w mm.

UWAGA:

Koła pasowe SPA/A patrz strona J 8 - J 10.


Pas klinowy B/17

Hi-Power® - profil klasyczny, spłaszczony



Materiał

Polichloropren



	Szer. b	Wys. h
B	17	11

B/17

Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość
F06236	B 25	650	F06273	B 71	1815	T37118	B 133	3390
F06237	B 26	670	F06274	B 72	1850	T37120	B 134	3415
F06238	B 27	695	F06275	B 73	1865	T37124	B 136	3460
F06239	B 27,5	710	F06276	B 74	1900	T18291	B 140	3550
F06240	B 28	725	F06277	B 75	1915	T37126	B 144	3670
F06241	B 29	750	F06278	B 76	1950	T18295	B 147	3750
F06242	B 30	775	F06279	B 77	1970	T37129	B 148	3770
F06243	B 31	800	F06280	B 78	2000	T37132	B 152	3870
F06244	B 32	825	F03101	B 79	2020	T18300	B 157	4000
F06245	B 33	850	F06281	B 80	2040	T37133	B 158	4025
F06246	B 34	875	F06282	B 81	2060	T37137	B 162	4125
F06247	B 35	900	F06283	B 82	2100	T35346	B 165	4200
F06248	B 36	925	F06284	B 83	2120	T18301	B 167	4250
F05276	B 37	950	F06285	B 84	2145	T37139	B 173	4400
F06249	B 38	975	F06286	B 85	2160	F06311	B 175	4450
F06250	B 39	1000	F06287	B 86	2200	T18302	B 177	4500
F05097	B 40	1030	F06288	B 87	2220	T37141	B 180	4580
F06251	B 41	1060	F06289	B 88	2240	T18303	B 186	4750
F06252	B 42	1075	F06290	B 89	2270	T37142	B 195	4960
F06253	B 43	1100	F05386	B 90	2300	T18304	B 196	5000
F06254	B 44	1120	F05656	B 91	2325	F06312	B 204	5220
F06255	B 45	1150	F06291	B 92	2360	T35407	B 208	5300
F06256	B 46	1180	F06292	B 93	2375	T37143	B 210	5345
F06257	B 47	1200	F06293	B 94	2400	T35411	B 221	5600
F06258	B 48	1225	F06294	B 95	2425	T37145	B 225	5690
F05346	B 49	1250	F06295	B 96	2450	T37151	B 240	6070
F06259	B 50	1275	F06296	B 97	2475	T35424	B 249	6300
F05095	B 51	1300	F06297	B 98	2500	T37153	B 270	6830
F06260	B 52	1335	F06298	B 99	2525	T37155	B 300	7620
F06261	B 53	1360	F06299	B 100	2540			
F06262	B 54	1385	F06300	B 102	2600			
F05099	B 55	1400	F06301	B 103	2625			
F06263	B 56	1435	F05387	B 104	2650			
F06264	B 57	1460	F06302	B 105	2680			
F06265	B 58	1485	F06303	B 106	2700			
F06266	B 59	1500	F06304	B 108	2755			
F06267	B 60	1535	F06305	B 110	2800			
F05098	B 61	1560	F06306	B 112	2850			
F06268	B 62	1585	F06307	B 114	2900			
F04262	B 63	1600	F06308	B 116	2950			
F06269	B 64	1625	T09983	B 118	3000			
F05104	B 65	1650	T37115	B 120	3060			
F06270	B 66	1700	F06309	B 122	3100			
F05258	B 67	1725	T18282	B 124	3150			
F06271	B 68	1750	T18285	B 128	3250			
F05103	B 69	1765	F06310	B 130	3310			
F06272	B 70	1800	T18287	B 131	3350			

Rozmiary w mm

UWAGA:

Koła pasowe SPB/B patrz strona J 11 - J 14.


Pas klinowy C/22

Hi-Power® - profil klasyczny, spłaszczony



Materiał

Polichloropren



	Szer. b	Wys. h
C	22	14

C/22

Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość
F06313	C 42	1080	F06338	C 90	2300	T37172	C 144	3670
F06314	C 43	1100	F06339	C 92	2360	T37173	C 147	3750
F06315	C 46	1180	F06340	C 93	2375	T37174	C 153	3900
F06316	C 48	1230	F06341	C 95	2425	T37175	C 158	4000
F06317	C 49	1250	F06342	C 96	2460	T37176	C 162	4130
F06318	C 51	1320	F06343	C 97	2475	T37177	C 165	4200
F06319	C 53	1350	F06344	C 98	2500	T37178	C 173	4400
F06320	C 54	1375	F05155	C 99	2525	F06353	C 177	4500
F06321	C 55	1400	F06345	C 100	2560	T37180	C 180	4575
F06322	C 59	1500	F05154	C 102	2600	T37181	C 195	4980
F06323	C 60	1525	F06346	C 104	2650	T37182	C 208	5300
F04852	C 62	1600	F06347	C 105	2675	T37183	C 210	5340
F06324	C 65	1665	F06348	C 108	2750	T37184	C 222	5600
F06325	C 66	1700	F06349	C 110	2800	T37185	C 225	5675
F06326	C 68	1750	F06350	C 112	2860	T37186	C 238	6000
F06327	C 70	1800	F06351	C 115	2935	T37188	C 240	6050
F06328	C 71	1830	T37163	C 116	2965	T37189	C 250	6300
F06329	C 72	1840	T37164	C 118	3000	T37190	C 255	6440
F06330	C 74	1900	T37165	C 120	3050	T37191	C 265	6700
F06331	C 75	1920	T37166	C 124	3150	T37192	C 270	6820
F06332	C 78	2000	T37167	C 128	3250	T37193	C 280	7100
F06333	C 81	2070	F06352	C 130	3300	T37194	C 285	7200
F06334	C 82	2100	T37168	C 132	3350	T37195	C 300	7580
F06335	C 83	2120	T37169	C 134	3415	T37196	C 330	8340
F06336	C 85	2170	T37170	C 136	3450			
F06337	C 88	2240	T37171	C 140	3550			

Rozmiary w mm.

UWAGA:

Koła pasowe SPC/C patrz strona J 15 - J 16.


Pas klinowy D/32

Hi-Power® - profil klasyczny, spłaszczony



Materiał

Polichloropren



	Szer. b	Wys. h
D	32	19

D/32

Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość	Kod	Oznaczenie	Wew. długość
F06354	D 98	2500	T37206	D 162	4115	T37216	D 223	5600
F06355	D 104	2650	T37207	D 170	4320	T37217	D 240	6030
F01642	D 110	2800	T37208	D 173	4400	T37219	D 250	6300
T37199	D 120	3050	T37209	D 177	4500	T37220	D 270	6800
T37200	D 124	3150	T37210	D 180	4570	T37221	D 282	7100
T37201	D 128	3250	T37211	D 187	4750	T37218	D 298	7500
T37202	D 137	3480	T37212	D 195	4955	T37222	D 300	7555
T37203	D 140	3550	T37213	D 197	5000	T37223	D 330	8320
T37204	D 144	3660	T37214	D 204	5180	T37224	D 360	9080
T37205	D 158	4000	T37215	D 210	5335			

Rozmiary w mm.


Pas klinowy obustronny

Hi-Power® - Dubl-V, profil klasyczny, spłaszczony



Material

Polichloropren



	Szer. b	Wys. h
AA	13	8
BB	17	11

AA

Kod	Oznaczenie	Obliczeniowa długość ISO	Długość RMA	Kod	Oznaczenie	Obliczeniowa długość ISO	Długość RMA
T 40073	AA51	1330	1350	T 40092	AA 90	2325	2340
T 40074	AA55	1435	1450	T 40093	AA 92	2375	2390
T 40077	AA60	1560	1575	T 40095	AA 96	2475	2490
T 40079	AA68	1765	1780	T 40097	AA 105	2705	2720
T 40086	AA75	1940	1960	T 40099	AA 112	2880	2900
T 40088	AA80	2070	2085	T 40100	AA 120	3085	3100
T 40090	AA85	2195	2210	T 40102	AA 128	3290	3305

BB

T 40104	BB 35	940	965	T 40154	BB 116	3000	3020
T 40106	BB 38	1015	1040	T 40155	BB 118	3050	3070
T 40108	BB 42	1120	1140	T 40156	BB 120	3100	3120
T 40109	BB 43	1145	1165	T 40157	BB 122	3150	3170
T 40111	BB 45	1195	1215	T 40158	BB 123	3175	3195
T 40112	BB 46	1220	1240	T 40159	BB 124	3200	3225
T 40114	BB 51	1345	1370	T 40160	BB 127	3275	3300
T 40115	BB 53	1395	1420	T 40161	BB 128	3300	3325
T 40117	BB 55	1450	1470	T 40162	BB 129	3325	3350
T 40118	BB 60	1575	1600	T 40163	BB 130	3350	3375
T 40120	BB 68	1780	1800	T 40164	BB 136	3505	3525
T 40121	BB 71	1855	1880	T 40165	BB 144	3710	3730
T 40124	BB 73	1905	1930	T 40166	BB 155	3990	4010
T 40125	BB 74	1930	1955	T 40167	BB 158	4065	4085
T 40127	BB 75	1955	1980	T 40168	BB 168	4320	4340
T 40128	BB 81	2110	2130	T 40169	BB 169	4345	4365
T 40129	BB 85	2210	2235	T 40171	BB 173	4445	4470
T 40130	BB 90	2335	2360	T 40173	BB 180	4625	4645
T 40132	BB 92	2390	2410	T 40174	BB 195	5005	5025
T 40134	BB 93	2415	2435	T 40176	BB 210	5385	5410
T 40135	BB 94	2440	2460	T 40177	BB 226	5755	5775
T 40137	BB 97	2515	2540	T 40179	BB 228	5805	5825
T 40149	BB 105	2720	2740	T 40180	BB 230	5855	5875
T 40150	BB 107	2770	2790	T 40182	BB 240	6110	6130
T 40151	BB 108	2795	2815	T 40189	BB 270	6870	6895
T 40152	BB 111	2870	2895	T 40191	BB 277	7050	7070
T 40153	BB 112	2895	2920	T 40193	BB 300	7635	7665

Rozmiary w mm.

UWAGA:

Koła pasowe SPA/A patrz strona J 8 - J 10, koła pasowe SPB/B patrz strona J 11 - J 14.


Pas klinowy obustronny

Hi-Power® - Double-V, profil klasyczny, spłaszczony



Materiał

Polichloropren



	Szer. b	Wys. h
CC	22	14
DD	32	19

CC

Kod	Oznaczenie	Obliczeniowa długość ISO	Długość RMA	Kod	Oznaczenie	Obliczeniowa długość ISO	Długość RMA
T 40194	CC 75	1980	2010	T 40219	CC 162	4190	4220
T 40196	CC 81	2130	2165	T 40220	CC 173	4465	4500
T 40197	CC 85	2230	2265	T 40225	CC 180	4645	4680
T 40200	CC 90	2360	2395	T 40226	CC 195	5025	5060
T 40202	CC 96	2510	2545	T 40227	CC 210	5405	5440
T 40204	CC 105	2740	2775	T 40229	CC 240	6120	6150
T 40206	CC 112	2920	2950	T 40231	CC 270	6880	6915
T 40208	CC 120	3120	3155	T 40233	CC 300	7640	7675
T 40210	CC 128	3325	3360	T 40234	CC 330	8405	8440
T 40213	CC 136	3525	3560	T 40236	CC 360	9165	9200
T 40214	CC 144	3730	3765	T 40238	CC 390	9930	9960
T 40216	CC 158	4085	4120	T 40240	CC 420	10690	10725

DD

T 40242	DD 210	5415	5465	T 40244	DD 300	7635	7690
T 40243	DD 270	6875	6925	T 40246	DD 360	9160	9215

Rozmiary w mm.

UWAGA:

Koła pasowe SPC/C patrz strona J 15 - J 16.