



Tuleje mocujące Taper Lock®

Material

Żeliwo



4 otwory

Kod	Tuleja	Otwór wew.	Rowek		Długość	Ø
			Szer.	Wys.		
T 35934	1008	10	3	1.4	22.3	0.15 aż 0.08
T 29702		11	4	1.8		
T 31007		12	4	1.8		
T 31008		14	5	2.3		
T 31009		16	5	2.3		
T 31010		18	6	2.8		
T 31011		19	6	2.8		
T 31012		20	6	2.8		
T 31013		22	6	2.8		
T 31014		24	8	1.3*		
T 31015		25	8	1.3*		
T 35935	1108	10	3	1.4	22.3	0.18 do 0.10
T 31016		11	4	1.8		
T 31017		12	4	1.8		
T 31018		14	5	2.3		
T 31020		16	5	2.3		
T 31021		18	6	2.8		
T 31022		19	6	2.8		
T 31023		20	6	2.8		
T 31024		22	6	2.8		
T 31025		24	8	3.3		
T 31026		25	8	3.3		
T 31027	28	8	1.3*			
T 31028	1210	11	4	1.8	25.4	0.30 do 0.17
T 31029		12	4	1.8		
T 31030		14	5	2.3		
T 31032		16	5	2.3		
T 31033		18	6	2.8		
T 31034		19	6	2.8		
T 31035		20	6	2.8		
T 31036		22	6	2.8		
T 31037		24	8	3.3		
T 31038		25	8	3.3		
T 31039		28	8	3.3		
T 31040		30	8	3.3		
T 31041		32	10	3.3		
T 31066		1610	14	5		
T 31067	15		5	2.3		
T 31068	16		5	2.3		
T 31069	18		6	2.8		
T 31070	19		6	2.8		
T 31071	20		6	2.8		
T 31072	22		6	2.8		
T 31073	24		8	3.3		
T 31074	25		8	3.3		
T 31075	28		8	3.3		
T 31076	30		8	3.3		
T 31077	32	10	3.3			

Kod	Tuleja	Otwór wew.	Rowek		Długość	Ø
			Szer.	Wys.		
T 31078	1610	35	10	3.3		0.42 do 0.20
T 31079		38	10	3.3		
T 31080		40	12	3.3		
T 31081		42	12	3.3		
T 31082		14	5	2.3		
T 31083	16	5	2.3			
T 31084	18	6	2.8			
T 31085	19	6	2.8			
T 31086	20	6	2.8			
T 31087	22	6	2.8			
T 31088	24	8	3.3			
T 31089	25	8	3.3			
T 31090	28	8	3.3			
T 31091	30	8	3.3			
T 31092	32	10	3.3			
T 31093	35	10	3.3			
T 31094	38	10	3.3			
T 31095	40	12	1.3*			
T 31096	42	12	1.3*			
T 35936	2012	14	5	2.3	31.8	0.80 do 0.38
T 31098		16	5	2.3		
T 31099		18	6	2.8		
T 31100		19	6	2.8		
T 31101		20	6	2.8		
T 31102		22	6	2.8		
T 31103		24	8	3.3		
T 31104		25	8	3.3		
T 31105		28	8	3.3		
T 31106		30	8	3.3		
T 31107		32	10	3.3		
T 31108		35	10	3.3		
T 31109		38	10	3.3		
T 31110		40	12	3.3		
T 31111	42	12	3.3			
T 31112	45	14	3.8			
T 31113	48	14	3.8			
T 31114	50	14	3.8			
T 35937	2517	16	5	2.3	44.5	1.7 do 0.8
T 35938		18	6	2.8		
T 31115		19	6	2.8		
T 31116		20	6	2.8		
T 31117		22	6	2.8		
T 31118		24	8	3.3		
T 31119		25	8	3.3		
T 31120		28	8	3.3		
T 31121		30	8	3.3		
T 31122		32	10	3.3		
T 31123		35	10	3.3		

Rozmiary w mm.


UWAGA:

* Otwór wew z płaskim klinkiem.


Tuleje mocujące Taper Lock®

Material

Żeliwo



4 otwory



5 otworów

Kod	Tuleja	Otwór wew.	Rowek		Dług.	kg
			Szer.	wys.		
T 31124	2517	38	10	3.3	44.5	1.7 do 0.8
T 31125		40	12	3.3		
T 31126		42	12	3.3		
T 31127		45	14	3.8		
T 31128		48	14	3.8		
T 31129		50	14	3.8		
T 31130		55	16	4.3		
T 31131		60	18	4.4		
T 31133	3020	25	8	3.3	50.8	2.8 do 1.5
T 31134		28	8	3.3		
T 31135		30	8	3.3		
T 31136		32	10	3.3		
T 31137		35	10	3.3		
T 31138		38	10	3.3		
T 31139		40	12	3.3		
T 31140		42	12	3.3		
T 31141		45	14	3.8		
T 31142		48	14	3.8		
T 31143		50	14	3.8		
T 31144		55	16	4.3		
T 31145		60	18	4.3		
T 31146		65	18	4.3		
T 31147		70	20	4.9		
T 31148	75	20	4.9			
T 31149	3030	35	10	3.3	76.2	4.0 do 2.1
T 31150		38	10	3.3		
T 31151		40	12	3.3		
T 31152		42	12	3.3		
T 31153		45	14	3.8		
T 31154		48	14	3.8		
T 31155		50	14	3.8		
T 31156		55	16	4.3		
T 31157		60	18	4.4		
T 31158		65	18	4.4		
T 31159		70	20	4.9		
T 31160	75	20	4.9			
T 35939	3525	35	10	3.3	64.0	5.5 do 1.8
T 35940		38	10	3.3		
T 35941		40	12	3.3		
T 35942		42	12	3.3		
T 35943		45	14	3.8		
T 35944		48	14	3.8		
T 35945		50	14	3.8		

Kod	Tuleja	Otwór wew.	Rowek		Dług.	kg
			Szer.	Wys.		
T 35946	3525	55	16	4.3	64.0	5.5 do 1.8
T 35947		60	18	4.4		
T 35948		65	18	4.4		
T 35949		70	20	4.9		
T 35950		75	20	4.9		
T 35951		80	22	5.4		
T 35952		85	22	5.4		
T 35953		90	25	5.4		
T 35954		95	25	5.4		
T 35955		100	28	4.4*		
T 31161	3535	35	10	3.3	88.9	6.6 do 3.2
T 31162		38	10	3.3		
T 31163		40	12	3.3		
T 31164		42	12	3.3		
T 31165		45	14	3.8		
T 31166		48	14	3.8		
T 31167		50	14	3.8		
T 31168		55	16	4.3		
T 31169		60	18	4.4		
T 31170		65	18	4.4		
T 31171		70	20	4.9		
T 31172		75	20	4.9		
T 31173		80	22	5.4		
T 31174		85	22	5.4		
T 31176	90	25	5.4			
T 35956	4030	40	12	3.3	76.0	7.4 do 4.2
T 35957		42	12	3.3		
T 35958		45	14	3.8		
T 35959		48	14	3.8		
T 35960		50	14	3.8		
T 35961		55	16	4.3		
T 35962		60	18	4.4		
T 35963		65	18	4.4		
T 35964		70	20	4.9		
T 35965		75	20	4.9		
T 35966		80	22	5.4		
T 35967		85	22	5.4		
T 35968		90	25	5.4		
T 35969		95	25	5.4		
T 35970	100	28	6.4			
T 35971	105	28	6.4			
T 35972	110	28	6.4			
T 35973	115	32	5.4*			

Rozmiary w mm.

UWAGA:


* Otwór wew z płaskim klinkiem.

Od wielkości 3525 - tuleja mocująca z 5 otworami.

Tuleje mocujące Taper Lock®

Materiał

Żeliwo



5 otwrów

Kod	Tuleja	Otwór wew.	Rowek		Dług.	kg
			Szer.	Wys.		
T 35974	4040	40	12	3.3	101.6	10.1 do 5.2
T 35975		42	12	3.3		
T 35976		45	14	3.8		
T 31177		48	14	3.8		
T 31178		50	14	3.8		
T 31179		55	16	4.3		
T 31182		60	18	4.4		
T 31183		65	18	4.4		
T 31184		70	20	4.9		
T 31185		75	20	4.9		
T 31186		80	22	5.4		
T 31187		85	22	5.4		
T 31188		90	25	5.4		
T 31189		95	25	5.4		
T 31190		100	28	6.4		
T 35977	4535	55	16	4.3	89.0	10.7 do 4.2
T 35978		60	18	4.4		
T 35979		65	18	4.4		
T 35980		70	20	4.9		
T 35981		75	20	4.9		
T 35982		80	22	5.4		
T 35983		85	22	5.4		
T 35984		90	25	5.4		
T 35985		95	25	5.4		
T 35986		100	28	6.4		
T 35987		105	28	6.4		
T 35988		110	28	6.4		
T 35989		115	32	7.4		
T 35990		120	32	7.4		
T 35991		125	32	7.4		
T 31191	4545	55	16	4.3	114.3	13.2 do 7.4
T 31192		60	18	4.4		
T 31193		65	18	4.4		

Kod	Tuleja	Otwór wew.	Rowek		Dług.	kg
			Szer.	Wys.		
T 31194	4545	70	20	4.9	114.3	13.2 do 7.4
T 31195		75	20	4.9		
T 31196		80	22	5.4		
T 31197		85	22	5.4		
T 31198		90	25	5.4		
T 31199		95	25	5.4		
T 31200		100	28	6.4		
T 35992		105	28	6.4		
T 31201		110	28	6.4		
T 35993		5040	70	20		
T 35994	75		20	4.9		
T 35995	80		22	5.4		
T 35996	85		22	5.4		
T 35997	90		25	5.4		
T 35998	95		25	5.4		
T 35999	100		28	6.4		
T 36000	105		28	6.4		
T 36002	110		28	6.4		
T 36003	115		32	7.4		
T 36004	120	32	7.4			
T 36005	125	32	7.4			
T 31202	5050	70	20	4.9	127.0	15.2 do 9.2
T 31203		75	20	4.9		
T 31204		80	22	5.4		
T 31205		85	22	5.4		
T 31206		90	25	5.4		
T 31207		95	25	5.4		
T 31208		100	28	6.4		
T 36006		105	28	6.4		
T 31209		110	28	6.4		
T 36007		115	32	7.4		
T 31210		120	32	7.4		
T 31211		125	32	7.4		

Rozmiary w mm.

UWAGA:

* Otwór wewnętrzny z płaskim klinkiem.